



Injector Coefficient Database Instructions [356425]

EVINRUDE
E-TEC

OUTBOARDS
SERVICE
Bulletin

Suggested Routing:
☐ Service ☐ Sales ☐ Parts

Date: July 30, 2011

No. 2011-05(S)

MODELS: All Evinrude® E-TEC® 15–300 HP outboards, 1999–2001 Evinrude Ficht 75–250 HP outboards, and 2002–2006 Evinrude DI 75–250 HP outboards

SUBJECT: Injector Coefficient Database
Replaces Service Bulletin 2010-07(S)

Dear Evinrude/Johnson® Dealers:

This communication is to inform Evinrude and Johnson dealers of a change to the procedure of obtaining injector coefficient files.

Dealers can now download the coefficient files for new service fuel injectors from a database available on the internet.

SERVICE FUEL INJECTOR KITS

A change will be made to the following service fuel injector kits. This change:

- Removes the disk containing the coefficient files from the service fuel injector kits.
- Adds a "Checksum" (CS) number to the injector serial number label.

A service fuel injector **MUST** have a serial number and a checksum number on the serial number label to download coefficient files from the internet.

Coefficient files are **NOT** available on the internet for fuel injector kits that include a coefficient disk.

For assistance with coefficient file disks in the U.S. and Canada call 1-800-888-4662.

Dealers outside of North America should contact their regional office.

Evinrude E-TEC Models		
Kit P/N	Year	HP/Models
5007894	2009 & newer	15 – 30 HP Inline
5006220	2004 – 2007	40 – 90 HP Inline
5008826	2008 & newer	40 – 90 HP Inline (Includes 55 MFE)
5007042	2007	115 – 200 HP 60° V4/V6 (C, R, Suffix)
5007043		
5007179	2007	150 – 200 HP 60° V6 (F Suffix)
5007180		
5007764	2008 & newer	115 – 200 HP 60° V4/V6
5007765		
5006221	2005 – 2007	200 – 250 HP 90° V6 (3.3 L)
5006222		
5007764	2008 & newer	200 – 300 HP 90° V6 (3.3 L and 3.4 L)
5007765		

Evinrude DI Models		
Kit P/N	Year	HP/Models
5004478	1999	90–115 HP 60° V4 (C, N Suffix)
		150–175 HP 60° V6 (A, C, N Suffix)
5004479	1999 – 2000	150–175 HP 60° V6 (O, V Suffix)
5005195	2000 – 2006	75–175 HP 60° V4/V6
5004475	1999	200 – 225 HP 90° V6 (N, O Suffix)
5004476		
5004443	2000	200 – 250 HP 90° V6
5004444		
5005196	2001 – 2005	200 – 250 HP 90° V6
5005197		






PROCEDURE

Injector Information


Evinrude E-TEC Models: Refer to the serial number label attached to the fuel injector electrical connector.



1. Serial number
2. Checksum number

008318

Evinrude DI Models: Refer to the serial number label etched on the fuel injector housing.



1. Serial number
2. Checksum number

008339

ACCURATELY record the 14-digit Serial Number (SN) and the 5-digit Checksum (CS) number from the injector serial number label.

Record Injector Serial Number Below:													
Record Injector Checksum:													

IMPORTANT: Mistakes recording the serial number or checksum can result in downloading the incorrect coefficient file.

Download Coefficient Files

DealerPort Users

Log onto *DealerPort*. Select the "Engine Software" link. Select the "Outboard Injector Coefficient Database Utility" link.



1. "Engine Software" link
2. "Outboard Injector Coefficient Database Utility" link

008319

BossWeb Users

Log onto *BossWeb*. Select the "ComCenter" dropdown menu. Select the "E-TEC Injector Coefficient" link.



1. "ComCenter" dropdown menu
2. "E-TEC Injector Coefficient" link

008320

All Users

- 1) Enter the fuel injector 14-digit serial number in the "Serial Number" box.
- 2) Enter the fuel injector 5-digit checksum number in the "Checksum" box.

- 6) Select the "Save" button to save the file to this location.




3) Select the "Download Injector Coefficient File" button.



1. "Serial Number" box
2. "Checksum" box
3. "Download Injector Coefficient File" button

008321

4) When the "File Download" box appears, select the "Save" button.



1. "Save" button

008322

5) Save the file to a known location on the computer. A removable storage device may be used to transfer coefficient files to a service laptop if it is not internet capable.



1. Local disk
2. Removable disk
3. "Save" button

008323

Repeat steps 1 through 6 to download multiple coefficient files.


NOTICE All injectors must be installed in the correct cylinder by serial number. Improper injector installation can result in powerhead failure.

Upload Coefficient Files to EMM

Use the *Evinrude Diagnostics* software "Settings" screen to upload the coefficient file(s) to the EMM. Select the "Fuel Injectors" tab.

Select the cylinder tab for injector being replaced.

Select the "Replace Fuel Injector" button.




1. "Fuel Injectors" tab
2. "Cylinder" tabs
3. "Replace Fuel Injector" button

008118

Use the drop down menu to navigate to the saved coefficient file location. The coefficient file name matches the serial number of the service fuel injector.

Select the correct file for the service fuel injector.

Select the "Replace Fuel Injector" button to start the upload process.



1. Injector coefficient file
2. "Replace Fuel Injector" button

008335

An injector replacement "Attention" window will

appear. Select the "Yes" button to confirm injector replacement.



Injector Replacement Confirmation

008336

1. "Yes" button

After the upload is complete, the program will return to the "Cylinder" tab.

Confirm the serial number displayed on the cylinder tab matches the serial number printed on the serial number label of the service fuel injector.



1. *Serial number*

008338

